

DELTA 4200+

WWW.RKARA.IR



4" wide, 203dpi, 5ips, 4-in-1 interface, designed for a large supply of label printing.

Specification	DELTA 4200+
Print Method	Thermal Transfer, Direct Thermal
Paper Width	20~120mm
Print Width	108mm max.
Print Speed	2"~5" per second
Resolution	203DPI
Paper Type	Label, Continuous, Fanfold
Print length	2286mm(90") max
Roll Diameter	Internal: 25.4~127mm External with holder: 25.4~200mm
Paper Thickness	0.06~0.254mm
Paper Sensor	Label gap, Black mark, Notch
Interface	Serial,USB,Parallel, Ethernet
Memory	2MB SDRAM, 2MB FLASH
Ribbon Width	30~110mm
Ribbon Length	300meters
Emulation	Compatible with Zebra emulation
Barcode	Code 39,Code 93,ITF,EAN 128, Code 128 subsets A,B,C,Codabar, EAN-8,EAN-13,UPC-A,UPC-E, EAN and UPC 2(5) digits add-on, MSI,MSIC,PLESSEY,CPOST,ITF 14,EAN 14. QR Code(2D)
Graphic type	BMP, PCX
Character & Font	Chinese, Korean, 8-bit code page(437 United States, 850 Multilingual, 852 Slavic, 860 Portuguese, 863 Canadian, French, 865 Nordic); Windows code page(1250 Central Europe, Latin, 1253 Greek, 1254 Turkish)
Power	AC100~240V, 24VDC, 2A