



Model No.	Kiosk GPE310K
Print method	Direct thermal line
Print width	64/72mm
Dot density	512dot/line,576dot/line
Print speed	250mm/s
Interface	Serial+USB+Parallet
paper width	80±0.5mm
Paper diameter	150mm
Line space	3.75mm(can be adjusted by sending commands)
Paper loading	easy loading
Columns	Fondt A-42columns or 48columns/Font B-56columns or 64columns/Simplified/Traditional Chinese-21columns or 24columns
character Size	ANK Font Font A:12×24dots Font B:9×17dots simplified/Traditionl Chinese:24×24dots
Code page	PC437Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/pc858/IranII/Latvian/Arabic/PT 151,1251/PC737/WPC1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128
Fonts	GB18030
data	128K bytes
NV Flash	256Kbytes
Cashdrawer out	DC24V/1A
Power supply	DC24V/2A
Power adaptor	Input:AC 110V/220V,50~60Hz Output:DC24V/2A
Weight	1.70KG
Dimension	154×192.5×136mm(W×L×H)
Work environment	Temperature: 0°~45℃ Humidity:10~80%
Storage environment	Temperature: -10°~60℃ Humidity:10~90%
Mechanism	150Km
Auto cutter	15 million cuts