

Pos printer

Delta T80

Line Thermal Printer

Thermal receipt printer with high speed, attractive appearance, at the same time features with 300mm high speed, multi-interface in one printer, together with excellent 1D, 2D barcode printer ability, They can provide all features you will need.

Main Features:

- · Compatible with ESC/POS and Star commands
- Waterproof, oil-proof, dust-proof structure
- · Kitchen printing and netword printing supported
- · Network status monitoring, multilink printing
- OPOS/ Linux/ Win8 supporting
- · Printer authentication and software bundle
- High speed driver printing mode, serial port speed is 66% faster
- · Auto print recovering when network disconnected
- Virtual serial port for USB connection, USB port supports OPOS application
- 100MB network interface card makes the connection and print much faster, stop receipts misprinting





Support 2D Barcode printing 300mm/s ultra high speed

Technical Specifications

Model Number	Delta T80
Print method	Direct thermal line
Dot density	512dot/line, 576dot/line
Print speed	300mm/s
Interface	Serial+USB+Ethernet, Parallel+USB
Paper width	$79.5 \pm 0.5 \text{mm}$
Paper diameter	83mm
Paper thickness	0.06~0.08mm
Auto cutter	1.5 million cuts
Weight	1.23KG
Dimension (W x Lx H)	139×180.6×127mm
Work environment	Temperature: $0{\sim}45^{\circ}\mathrm{C}$, Humidity: $10{\sim}80\%$
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/
	CODE39/ITF/CODABAR/CODE93/CODE128
Character	ANK Character Font A: 12 \times 24dots Font B: 9 \times 17dots
	Chinese: 24×24dots
Driver	Windows 2000/2003/XP/Vista/7/0P0S/Linux
Power supply	DC 24V/2A
Reliability	150km
Fonts	GB18030
NV Flash	256K bytes
Data buffer	128K bytes
Storage environment	Temperature: -10 \sim 60 $^{\circ}$ C, Humidity: 10 \sim 90%



